



## Robur S2 Safes - 30P



### **Burglary protection**

Burglary-resistance – S2 according to EN 14450.  
Tested and certified by ECB·S.

### **Fire protection**

Fire-resistance – LFS 30P according to EN 15659.  
Tested and certified by ECB·S.

### **Description**

Designed to protect documents and valuables in case of fire or burglary

Thickness of door - 94 mm

Thickness of walls - 56 mm

### **Locking**

KL - Key lock

EL - Digital lock

### **Finish**

Off white, powder coating, RAL 9010.

### **Anchoring**

The safe is provided with holes for anchoring in the bottom.

### **Weight and measurements**

See overleaf.

# Dimensions in mms and kilos

model	<b>Robur S2-320/30</b>	<b>Robur S2-460/30</b>	<b>Robur S2-670/30</b>	<b>Robur S2-950/30</b>
External dimensions, mm				
Height	315	460	670	950
Width	445	440	440	440
Depth	440	440	440	440
Internal dimensions, mm				
Height	185	330	540	820
Width	334	329	329	329
Depth	290	290	290	290
Weight	52	68	91	120
Capacity, litre	18	31	51	78
Number of shelves	1	1	1	2

We reserve the right to alter the specification without prior notice.



**Head office**

**Robur Safe AB**

Lundbyvägen 8  
SE-310 50 SLÖINGE  
Phone: +46 346 260 260  
Fax: +46 346 260 222

[info@robursafe.com](mailto:info@robursafe.com)

[www.robursafe.com](http://www.robursafe.com)